DEVILBISS
AUTOMOTIVE REFINISHING

THE PRO PAINTERS PROCESS GUIDE

BREATHABLE AIR FILTRATION & CONTROL



- **A** First stage 5 micron filter element. Part No: PROAIR-51
- **B** Second stage 0.01 micron, breathing air filter element. Max oil carryover @ 20˚C of 0.01 mg/m3. Part No: PROAIR-52
- **C** Third stage 0.003 micron, breathing air filter element. Max oil carryover @ 20˚C of 0.003 mg/m3. Part No: PROAIR-53
- **D** Waist belt, breathing air, odour removal filter cartridge. Part No: PROV-27-K4

Replace filters A, B & C every 6 months, replace filter D every 3 months.

SPRAY TECHNICIAN RESPIRATORY PROTECTION





D



The DMG Aerodry guns significantly speed up waterborne drying times

i-system SPRAY GUNS & DIGITAL GAUGES



RECOMMENDED AIR CAP & FLUID TIP SET-UPS

COMPLIANT COATINGS

GPG FOR PRIMERS/FILLERS/SURFACERS





For full range of air caps and fluid nozzles see page 14

FOR WATER/ SOLVENT BASECOAT & CLEARCOAT

DV1





For full range of air caps and fluid nozzles see pages 4 & 6

PROLite





For full range of air caps and fluid nozzles see page 8

PROLite S

FOR SPOT, SMART & PANEL REPAIR





For full range of air caps and fluid nozzles see page 12